

## IN THE CLAIMS

1. (Currently Amended) A system for ~~use in~~ distributing authentication information to users of remote devices, comprising:

an authentication information store configured to store authentication information for a plurality of users;

an authentication system configured to receive a request for authentication information for one of the plurality of users from a remote device;

wherein the request ~~includes~~comprises identity information for use in determining whether the request is from one of the plurality of users,

wherein the authentication system retrieves based on the identity information the authentication information for the one of the plurality of users from the authentication information store;

wherein the retrieved authentication information is provided to the remote device.

2. (Currently Amended) The system of claim 1, wherein the authentication information is ~~to be~~ used in a two-factor authentication scheme.

3. (Currently Amended) The system of claim 1, wherein the authentication information store ~~includes~~comprises a seed store configured to store a plurality of seeds;

\_\_\_\_\_ wherein the authentication system is configured to receive a seed request, including an ~~access code generated using one of the plurality of seeds~~ from the remote device, to retrieve the one of the plurality of seeds from the seed store, to calculate an access code using the retrieved seed, to determine whether the calculated access code matches the received access

code, and to return the retrieved seed to the remote device where the calculated access code matches the received access code.

4. (Original) The system of claim 1, wherein the request comprises a Hypertext Transfer Protocol (HTTP) connection request.

5. (Currently Amended) The system of claim 1, wherein the request ~~includes~~comprises a network password and a digital signature, wherein the network password and digital signature are verified by the authentication system before the authentication information is provided to the remote device.

6. (Currently Amended) The system of claim 1, wherein the identity information ~~includes~~comprises user information and account information.

7. (Currently Amended) The system of claim 6, wherein the identity information identifies a particular user and corresponding authentication information being requested, and allows is used by the authentication system to authenticate the user requesting the authentication information.

8. (Currently Amended) The system of claim 1, wherein the identity information in the request ~~enables~~is used by the remote device for two-factor authentication ~~at the computer network~~.

9. (Currently Amended) The system of claim 8, wherein the identity information ~~includes~~comprises a network password entered by the user of the remote device and a digital

signature generated based on a transformation of at least a portion of the information in the request, a signature key, and a signature algorithm.

10. (Original) The system of claim 1, wherein the authentication system does not provide the authentication information to the remote device because a match was not found in the authentication information store based upon the identity information.

11. (Currently Amended) The system of claim 1, wherein the authentication information includes/comprises a password which is normally not known to the user of a remote device but is required for remote access to resources in the a computer network, wherein the password is known to a user of the remote device only for access to the resources in the computer network.

12. (Currently Amended) The system of claim 1, wherein the authentication information includes/comprises an access code which is normally not known to the user of a remote device but is required for remote access to resources in the a computer network, wherein the access code is known to a user of the remote device only for access to the resources in the computer network.

13. (Currently Amended) The system of claim 1, wherein the retrieved authentication information includes/comprises an expiring password which is valid for a relatively short period of time.

14. (Original) The system of claim 13, wherein the short period of time is on the order of minutes.

15. (Currently Amended) The system of claim 1, wherein the retrieved authentication information ~~includes~~comprises an expiring access code which is valid for a ~~relatively~~ short period of time.

16. (Currently Amended) The system of claim 1, wherein the retrieved authentication information ~~includes~~comprises a non-expiring password and is stored in a protected data store on the remote device.

17. (Currently Amended) The system of claim 1, wherein the retrieved authentication information ~~includes~~comprises a seed from which access codes are to be generated by the remote device, wherein the seed is stored in a protected data store on the remote device.

18. (Currently Amended) The system of claim 1, wherein the remote device uses the retrieved authentication information ~~is for use by the remote device~~ to gain access to a corporate local area network (LAN).

19. (Original) The system of claim 18, wherein two-factor authentication is used in the LAN to authenticate a user requesting remote access to the LAN, wherein the retrieved authentication information is used in performing two-factor authentication in order to gain access to the LAN.

20. (Currently Amended) The system of claim 19, wherein the retrieved authentication information ~~includes~~comprises a seed ~~for use by~~ which the remote device's two-factor code

generator uses to produce an access code, wherein the access code is also based upon a value provided by the remote device's clock, wherein the access code is used by the remote device to gain access to the LAN;

wherein the seed is used by the authentication system to also generate an access code for use in a comparison with the access code generated by the remote device;

wherein access to the LAN is either granted or denied based upon the comparison.

21. (Original) The system of claim 20, wherein the remote device only generates the access code when access to the LAN is requested by the user of the remote device.

22. (Currently Amended) The system of claim 20, wherein the authentication information store includes/comprises an index by user name that indicates users authorized for remote access to the LAN.

23. (Currently Amended) The system of claim 22, wherein the authentication information store stores user seed values from which access codes are to be generated ~~for use in generating access codes.~~

24. (Original) The system of claim 1, wherein the remote device is a wireless mobile communication device.

25. (Original) The system of claim 24, wherein the remote device stores the authentication information in a data store.

26. (Original) The system of claim 25, wherein the data store is implemented in a smart card.
27. (Original) The system of claim 25, wherein the data store is implemented in a Universal Serial Bus (USB) token.
28. (Original) The system of claim 1, wherein the remote device is a desktop computer.
29. (Currently Amended) The system of claim 1, wherein the remote device communicates with the authentication system over a communication system, wherein the communication system ~~includes~~ comprises a wide area network (WAN) and a wireless network gateway.
30. (Currently Amended) A method of distributing authentication information for remotely accessing computer resources, comprising: ~~the steps of:~~  
receiving a request for the authentication information from a remote device, the request comprising identity information of a user of the remote device;  
wherein the authentication information is stored in an authentication data store;  
authenticating the user based on the identity information in the request; and  
returning the authentication information to the remote device so that the remote device may access the computer resources based upon the returned authentication information.
31. (Currently Amended) An apparatus for use in handling authentication information for users of remote devices, comprising:

an authentication information store configured to store authentication information for a user of a remote device, the authentication information provided by a remote authentication system;

wherein a request for the authentication information from the remote device to the remote authentication system contains identity information;

wherein the authentication information that is stored in a data store by the remote authentication system is provided to the remote device after the request is processed based upon the identity information contained in the request;

a code generation system configured to retrieve the authentication information stored in the authentication information store;

wherein access information is generated based upon the retrieved authentication information and is used in accessing a remote computer network.

32. (Currently Amended) A method for obtaining authentication information for use in remotely accessing a computer network, the method comprising: ~~the steps of:~~

providing a request from a user of a remote device to an authentication system for the authentication information that is stored in a data store by the authentication system;

wherein the request ~~includes~~comprises identity information for use by the authentication system to authenticate the user based on the identity information provided in the request;

receiving by the remote device the authentication information from the authentication system;

wherein the received authentication information is to be used by the remote device to access the computer network.